Woodland Collection Specs





Modular Tile

Construction

Tufted, Textured Loop

Tile Size

50 cm x 50 cm (19.7" x 19.7") 25 cm x 1 m (9.84" x 39.4")

Yarn Type

EnduraStran Pro Nylon

Stain Resist / Soil Release

Stain-resistant and Soilreleasing EnduraStran Pro Nylon

Dye Method

Precision Point

Gauge

1/10

Stitches Per Inch

14.4

Tufts

144.0/in² (2,230/100 cm²)

Finished Pile Thickness

0.084" (2.13 mm)

Standard Backing

PVC-Free, Non-reactive, Breathable Backing

Recycled Content by Total Weight

Standard Backing NSF 140 Gold: 50.9% Pre-Consumer, 0.0% Post-Consumer

NSF 140 Platinum Backing Option: 40.0% Pre-Consumer, 10.8% Post-Consumer

Embodied Carbon

13.5 (kg CO_2e)/m²

Nominal Total Thickness

0.310" (7.9 mm)

Nominal Total Weight

86.7 oz/yd² (2,940 g/m²)

Flammability (Radiant Panel

ASTM-E-648) ≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or ASTM-E-662)

A3 | WI-E-002

 ≤ 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859

Self-Extinguishing

Lightfastness (AATCC 16E)

 \geq 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H.,70° F.

≤ 3.5 KV, Permanent Conductive Fiber

Texture Appearance Retention Rating (TARR)

Severe Traffic End-Use Applications

Recommended Maintenance

Visit millicare.com

Indoor Air Quality—CRI Green Label Plus™

Plus'[™]

GLP0793, Carpet Category 5Y

Recommended Installation Method(s)

Squares: Ashlar; Planks: All Methods

WARRANTIES

Lifetime Face Fiber Wear Lifetime Antistatic Lifetime Floor Compatibility Lifetime Color Pattern Permanency Lifetime Floor Release















Declare.

Lifetime Tuft Bind Lifetime Edge Ravel Flammability

This cushion-back carpet plank product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.